

INTEX 8+2 UPLINK



FEATURES

- 8*10/100 mbps.
- 2* 10/100 mbps.
- Uplink port up to 250 mtr
- Support IEEE 802.3 AF/AT
- Whole Power : $\leq 96W$
- All Supported by MDI/MDIX Auto flip

TECHNICAL SPECIFICATIONS

Product	8+2 UPLINK PoE
PoE Port	1 to 8 Support IEEE 802.3 AF/AT Standard
Output Power	15.4W/30W IEEE 802.3 af/at
Whole Power	$\leq 96W$ (52V 2.3A)
PoE Protocol	IEEE 802.3 af/ IEEE 802.3 at
PoE Type	End-span
Power Distance	1-8 port up to 90 mtr 9-10 port up to 250 mtr
Network Standard	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3 af/at
Network Medium	10/100 BASE-TX:5 class and above non shielded twisted pair
Switch Capability	1.6 Gbps
Forwarding Rate	100Mbps: 14880pps
MAC Address	MAC address table 2K
Port Function	Power priority mechanism, fast and forward, MAC automatic learning and aging IEEE 802.3x Full-duplex and mode and backpressure for Half-duplex mode
LED Indicator	LINK/ACT.100Mbps, PoE status Indicator, Power Indicator, Extender
Working Environment	Working Temperature : 10° C – 55° C