

INTEX DVR 16CH(IN-DVR-1602U-P1)



FEATURES

- 5-In-1 DVR(AHD, TVI, CVI,CVBS, IP)
- H.264/H.265 Smart Compression Technology
- Support 2Way Audio
- Remote View : Support P2P, Android / iOS / P//C
- Storage : 2 SATA (Up to 16TB)



H.264/H.265



VIDEO/AUDIO
CONTROL



24X7
RECORDING



P2P



2 SATA



MOBILE
APP

TECHNICAL SPECIFICATIONS

Processor	Industrial-grade processor
Operation system	Embedded LINUX operation system
Video Compression	H.264/H.265
Video Surveillance Quality	VGA(Max 1080P); HDMI(Max2K)
Video Preview	16*5MN@12fps/16*4MN@15fps/16*1080p@30fps
Video Code Capacity	16*5MN@5fps/16*4MN@8fps/16*1080N@15fps
Video Decode Capacity	16*5MN@5fps/16*D1@12fps
Input Mode	Coaxial: 16*5MP-N Mixed: 4MP-N(Coaxial)+1080P (IP) Arbitrary combination for coaxial and IP mode IP: 8*5MP, 16*5MP for all IP mode
Recognize Method	Automatic Identification: All AHD, All TVI, All CVI, Customized
Motion Detection	Testing areas can be set for each image
Audio Compression	G.711U
Audio Output	HDMI, support extended audio output.
Audio Input	Can Extend to 16CH Audio In
Intercom	Support extend audio In and Out intercom
Coaxial Audio	Support 16Ch coaxial audio
Record Video Mode	Manual, Alarm, Timing
Local Playback	16CH local playback

Playback Mode	Fast playback, Playback by Time, AI Playback, Smart playback, Advanced Intelligent playback
Storage Occupation	1080P 10-15G/day*channel; 720P 10G/day*channel; 960H 6-10G/day*channel;Audio:691M/day*channel
Record Storage	Local Hard Disc, Network
Backup Mode	USB, SATA Record, Network backup
Platform Access	Support (iOS, Android, PC)
Camera OSD Control	Support
3 DNR	Support auto/manual setting for noise reduction parameters.
Video Input Port	16CH BNC; support coaxial audio In
Video Output	1CH VGA, 1CH HDMI
Audio Output	HDMI output/Extended 1CH RCA audio output
Network Port	RJ45 10M/100M self-adapt to interface
USB Port	2 USB 2.0 port
HDD Port	2 SATA port(Can support Up to 16TB)
Power	12V/2A
Power Consumption	<15W (Exclusive Hard Disk)
Temperature	-5°C - +55°C
Working Humidity	10% - 90%